



Model Number 086D20	ICP® IMPACT HAMMER			Revision: H ECN #: 44362										
Performance	ENGLISH	SI		OPTIONAL VERSIONS Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. T - TEDS Capable of Digital Memory and Communication Compliant with IEEE P1451.4 TLD - TEDS Capable of Digital Memory and Communication Compliant with IEEE 1451.4 Output Bias Voltage 8.5 to 15 VDC 8.5 to 15 VDC										
Sensitivity(± 15 %)	1 mV/lbf	0.23 mV/N												
Measurement Range	± 5000 lbf pk	± 22,240 N pk												
Resonant Frequency	≥ 12 kHz	≥ 12 kHz												
Non-Linearity	≤ 1 %	≤ 1 %												
Electrical														
Excitation Voltage	20 to 30 VDC	20 to 30 VDC												
Constant Current Excitation	2 to 20 mA	2 to 20 mA												
Output Impedance	<100 Ohm	<100 Ohm	[1]											
Output Bias Voltage	8 to 14 VDC	8 to 14 VDC												
Discharge Time Constant	≥ 1400 sec	≥ 1400 sec	[1]											
Physical														
Sensing Element	Quartz	Quartz		NOTES: [1]Typical. [2]See PCB Declaration of Conformance PS136 for details.										
Sealing	Hermetic	Hermetic												
Hammer Mass	2.4 lb	1.1 kg												
Head Diameter	2.0 in	5.1 cm		SUPPLIED ACCESSORIES: Model 084A60 Tip - super soft plastic, gray (1) Model 084A61 Tip - soft plastic, brown (1) Model 084A62 Tip - medium plastic, red (1) Model 084A63 Tip - hard plastic, black (1) Model HCS-2 Calibration of Series 086 instrumented impact hammers (1)										
Tip Diameter	2.0 in	5.1 cm												
Hammer Length	14.5 in	37 cm												
Electrical Connection Position	Bottom of Handle	Bottom of Handle												
Electrical Connector	BNC Jack	BNC Jack												
<table border="1" style="width: 100%;"> <tr> <td style="width: 20%;">Entered: JM</td> <td style="width: 20%;">Engineer: NJF</td> <td style="width: 20%;">Sales: RWM</td> <td style="width: 20%;">Approved: NJF</td> <td style="width: 20%;">Spec Number:</td> </tr> <tr> <td>Date: 6/29/2015</td> <td>Date: 6/29/2015</td> <td>Date: 6/29/2015</td> <td>Date: 6/29/2015</td> <td style="text-align: center;">12923</td> </tr> </table>					Entered: JM	Engineer: NJF	Sales: RWM	Approved: NJF	Spec Number:	Date: 6/29/2015	Date: 6/29/2015	Date: 6/29/2015	Date: 6/29/2015	12923
Entered: JM	Engineer: NJF	Sales: RWM	Approved: NJF	Spec Number:										
Date: 6/29/2015	Date: 6/29/2015	Date: 6/29/2015	Date: 6/29/2015	12923										
 [2] All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice. ICP® is a registered trademark of PCB Group, Inc.				 Phone: 716-684-0001 Fax: 716-684-0987 E-Mail: info@pcb.com										



Represented in India by
Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029