

Model Number 1204-13A	LOW PROFILE LOAD CELL			Revision: B ECN #: 43809
Performance	ENGLISH	SI		OPTIONAL VERSIONS
Measurement Range	50 klbF	222 kN	[6][7]	Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used. 1204-13B - PC04E-10-6P Connector 1204-13C - PT02E-12-8P Connector 1204-13D - PC01E-12-8P Connector
Sensitivity(± 10 %)(RO)	4.0 mV/V	4.0 mV/V	[3][1]	
Non-Linearity	≤ 0.05 % FS	≤ 0.05 % FS	[6][8]	
Hysteresis	≤ 0.06 % FS	≤ 0.06 % FS	[6][8]	
Non-Repeatability	≤ 0.01 %RO	≤ 0.01 %RO	[3][8]	
Eccentric Load Sensitivity	0.25 %/in	0.25 %/25.4mm	[8]	
Resonant Frequency	15 kHz	15 kHz		
Side Load Sensitivity	0.25 %/in	0.25 %/25.4mm	[8]	
Creep(in 20 minutes)	0.025 %	0.025 %	[8]	
Static Error Band	≤ 0.05 % FS	≤ 0.05 % FS	[6][8]	
Environmental				NOTES:
Overload Limit	75 klbF	334 kN		[1]Nominal.
Load Limit(Side Force, F _X or F _Y)	25 klbF	111 kN	[4]	[2]Calibrated at 10 VDC, usable 5 to 20 VDC or VAC RMS.
Load Limit(Bending Moment, M _X or M _Y)	25 klbF-in	2825 Nm	[4]	[3]RO - Rated Output.
Load Limit(Axial Torque, M _Z)	25 klbF-in	2825 Nm	[4]	[4]Singularly applied, i.e. no other extraneous loads.
Temperature Range(Operating)	-65 to +200 °F	-54 to +93 °C		[5]Over compensated operating temperature range.
Temperature Range(Compensated)	+15 to +115 °F	-9 to +46 °C		[6]FS - Full Scale.
Temperature Effect on Output(Maximum)	± 0.0008 %Reading/°F	± 0.0018 %Reading/°C	[5]	[7]Calibrated in tension and compression.
Temperature Effect on Zero Balance(Maximum)	± 0.0008 %FS/°F	± 0.0018 %FS/°C	[5]	[8]Performance specifications guaranteed with factory installed optional Tension Base 084A101
Electrical				[9]See Outline Drawing 49932 for Complete Dimensions
Bridge Resistance	350 Ohm	350 Ohm	[1]	OPTIONAL ACCESSORIES:
Excitation Voltage(Recommended)	10 VDC	10 VDC	[2]	Model 084A101 TENSION LOAD BASE W/ 1.25-12 THD.
Insulation Resistance	>5K GOhm	>5K GOhm		Model 084A56 Pre-Tension Stud
Zero Balance	± 1 %RO	± 1 % FS	[3]	Model 084A90 Connector Shroud
Output Polarity	+Tension	+Tension		Model 181-012A PT06A-10-6S(SR)
Physical				Model 8311-01-10A CABLE
Size (Diameter x Height)	6.06 in x 3.50 in	153.9 mm x 88.9 mm	[9]	
Weight	21 lb	9.53 kg		
Mounting Thread	1 1/4 - 12 UNF-3B	No Metric Equivalent		
Housing Material	Painted Steel	Painted Steel		
Sensing Element	Strain Gage	Strain Gage		
Mounting Torque	1400 lbf-in	158 Nm		
Deflection at Full Scale Capacity	0.002 in	0.05 mm		
Electrical Connector	PT02E-10-6P	PT02E-10-6P		
<p><i>All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.</i></p>				
Entered: AP		Engineer: PE		Spec Number:
Date: 2/16/2015		Date: 2/16/2015		56135
<p>PCB Load & Torque, Inc. 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: Itinfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com</p>				



Represented in India by

Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029