


Model Number 5302D-01A	TORKDISC® ROTARY TORQUE SENSING SYSTEM			Revision: B ECN #: 44198
Performance	ENGLISH	SI		OPTIONAL VERSIONS
Measurement Range(Full Scale Capacity)	2000 in-lb	226 Nm		Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.
Accuracy	± 0.10 % FS	± 0.10 % FS	[3]	
Frequency Range(-3 dB)	0 to 8500 Hz	0 to 8500 Hz		
Filter Type(High Pass)	2-pole Butterworth	2-pole Butterworth	[4][5]	
Filter Type(Low Pass - Anti Alias)	8-pole Elliptical	8-pole Elliptical		
Voltage Output(channel A - AC coupled)	± 10 V	± 10 V		
Voltage Output(channel B - DC coupled)	± 10 V	± 10 V		
Gain(Channel A)	1-16 dB	1-16 dB		
Gain(Channel B)	0.3-1.3 dB	0.3-1.3 dB		
Digital Output	QSPI	QSPI	[6]	
Maximum Load(Axial)	500 lb	2.2 kN	[7][8]	NOTES: [1]Supplied with universal AC power adaptor. [2]Bolt joint slip torque is calculated assuming a coefficient of friction (μ) of 0.1 and that grade 8 socket head cap screws are used and tightened to 30% of yield. [3]Root sum square of non-linearity, hysteresis, and non repeatability. [4>Selectable High Pass cutoff frequencies of 5, 10, 20, 200 and 500 Hz. [5>Selectable Low Pass cutoff frequencies of 10,000, 5000, 2500, 1200, 625 and 313 Hz. [6]Request Technical Note FTQ-STN5 regarding digital output signal. [7]Extraneous load limits reflect the maximum axial load, lateral load, and bending moment that may be applied singularly without electrical or mechanical damage to the sensor. [8]Where combined extraneous loads are applied, decrease loads proportionally. [9]See PCB Declaration of Conformance PS069 for details.
Maximum Load(Lateral)	500 lb	2.2 kN	[7][8]	
Maximum Moment	1500 in-lb	169 Nm	[7][8]	
Environmental				
Overload Limit(Bolt Joint Slip)	3300 in-lb	373 Nm	[2]	
Overload Limit(Failure)	8000 in-lb	904 Nm		
Overload Limit(Safe)	6000 in-lb	678 Nm		
Temperature Range(Rotor/Stator - Operating)	+32 to +185 °F	0 to +85 °C		
Temperature Range(Rotor - Compensated)	+70 to +170 °F	+21 to +77 °C		
Temperature Range(Receiver - Operating)	0 to +122 °F	-17.7 to 50 °C		
Temperature Effect on Output(System - within compensated range)	0.002 %FS/°F	0.0036 %FS/°C		
Temperature Effect on Zero Balance(System - within compensated range)	0.002 %FS/°F	0.0036 %FS/°C		
Position Sensitivity(180° rotation of sensor)	≤ 0.1 % FS	≤ 0.1 % FS		
Electrical				SUPPLIED ACCESSORIES: Model 012AC024AT Cable (1) Model 182-028A Connector (1) Model M0003978 Power supply (1)
Power Required(50 to 60 Hz)	9 to 18 VDC	9 to 18 VDC	[1]	
Digital Resolution	16 Bit	16 Bit		
Digital Sample Rate	26,484 samples/sec	26,484 samples/sec		
Analog Resolution(based on ±10 V FSO and 16-bit resolution)	0.31 mV	0.31 mV		
Physical				
Maximum Speed	15,000 RPM	15,000 RPM		
Permissible Axial Float(rotor to stator)	0.25 in	6.4 mm		
Permissible Radial Float(rotor to stator)	0.25 in	6.4 mm		
Rotating Inertia(without adaptors)	0.056 in-lb/sec ²	0.006 N-m/sec ²		
Dynamic Balance	per ISO G 2.5	per ISO G 2.5		
Torsional Stiffness	5,800,000 in-lb/radian	655,312 N-m/radian		
Torsional Angle(at Full Scale Capacity)	0.020 °	0.020 °		
Housing Material(Sensor)	Anodized Aluminum	Anodized Aluminum		
Weight(rotor/sensor)	3.5 lb	1.6 kg		
				
[9]				
All specifications are at room temperature unless otherwise specified. In the interest of constant product improvement, we reserve the right to change specifications without notice.				
Entered: AP		Engineer: JM	Sales: KWW	Approved: JSD
Date: 5/13/2015		Date: 5/13/2015	Date: 5/13/2015	Date: 5/13/2015
				40425
			PCB Load & Torque 24350 Indoplex Circle Farmington Hills, MI 48335 UNITED STATES Phone: 866-684-7107 Fax: 716-684-0987 E-Mail: linfo@pcbloadtorque.com Web site: http://www.pcbloadtorque.com	



Represented in India by
Structural Solutions Pvt Ltd. | Phone: 040 2322 2380 | Email: sales@stsols.com

#4th Floor, Sudheer Tapani Towers, Himayath Nagar, Hyderabad - 500 029